

Light efficiency:



Light quality:



Color temperature:



Output: 1157 lm

Peak: 2349 cd


Power: 35.6 W

PF: 0.98



NU4-RAPH-XTM09-20LM-30K-83-30D-DL-WH

Date and time:
1/4/2022 1:47:00 PM




Beam angle

40°






CIE 1931
x: 0.445
y: 0.406

Spectra




Power






TM30: 84.8



CRI: 83.5 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.6	90.0	96.9	82.2	81.5	87.5	84.9	63.6	17.7	77.3	81.2	74.7	83.2	98.2	75.1


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
81.9	81.9	76.5	84.9	89.3	89.6	83.0	91.1	88.9	86.6	83.3	85.4	88.9	83.3	82.7	80.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
77.3	96.0	83.1	81.3	83.0	81.9	82.2	85.7	95.8	88.1	85.2	83.3	82.9	73.6	74.7

CQS: 82.4



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2880 K	83.5	17.7	84.8	98.4	82.4	0.445	0.406	0.255	0.349	-0.0004







Rf 84.8


Fidelity index Rf

Rg 98.4

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	82	-10%	-2%
2	82	-8%	7%
3	76	-2%	12%
4	85	4%	10%
5	89	7%	5%
6	90	6%	-3%
7	83	1%	-11%
8	91	-3%	-5%
9	89	-6%	-2%
10	87	-6%	5%
11	83	-3%	11%
12	85	5%	5%
13	89	6%	-4%
14	83	6%	-12%
15	83	0%	-11%
16	81	-7%	-14%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2346lx	586lx	261lx	147lx	94lx	65lx	48lx	37lx	29lx	23lx	19lx	16lx	14lx	12lx	10lx	9lx	8lx	7lx	6lx	6lx
217.9fcd	54.5fcd	24.2fcd	13.6fcd	8.7fcd	6.1fcd	4.4fcd	3.4fcd	2.7fcd	2.2fcd	1.8fcd	1.5fcd	1.3fcd	1.1fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.5fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2346	2329	2287	2217	2112	1979	1821	1646	1460	1274	1087	907	739	588	457	355	271	200	138	85
100%	99%	98%	94%	90%	84%	78%	70%	62%	54%	46%	39%	32%	25%	19%	15%	12%	9%	6%	4%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2346	2331	2285	2213	2118	2003	1872	1726	1573	1412	1249	1086	922	772	633	507	393	295	216	159
100%	99%	97%	94%	90%	85%	80%	74%	67%	60%	53%	46%	39%	33%	27%	22%	17%	13%	9%	7%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2346	2329	2287	2217	2112	1979	1821	1646	1460	1274	1087	907	739	588	457	355	271	200	138	85
100%	99%	98%	94%	90%	84%	78%	70%	62%	54%	46%	39%	32%	25%	19%	15%	12%	9%	6%	4%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2346	2331	2285	2213	2118	2003	1872	1726	1573	1412	1249	1086	922	772	633	507	393	295	216	159
100%	99%	97%	94%	90%	85%	80%	74%	67%	60%	53%	46%	39%	33%	27%	22%	17%	13%	9%	7%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
40°	68.4°	83°	99.6%	99.1%