

Light efficiency:

83 Lumen/Watt

Light quality:

CRI: 79.8

Color temperature:

2908 K

Output: 2212 lm

Peak: 1822 cd

Power: 26.6 W

PF: 1.0



Beam angle


70.5°

Product name:

NU3-QD-XTM19-27LM-30K-83-D65-120-Dim10-RET-WH-WH


Date and time:

8/29/2017 2:08:40 PM





CIE 1931
x: 0.448
y: 0.415


Spectra




Color details



TM30: 78.9



CRI: 79.8 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
77.4	85.4	93.5	79.7	76.6	80.8	84.6	60.4	6.4	67.0	77.9	63.4	78.4	96.0	70.2

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
76.4	76.7	69.2	75.6	82.5	84.7	72.9	85.9	81.4	79.8	77.2	80.2	86.6	81.7	76.2	79.0

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	x	y	u	v	Δuv
2908 K	79.8	6.4	78.9	98.1	0.448	0.415	0.253	0.352	0.0028

TM30 details







Rf 78.9

Fidelity index Rf


Rg 98.1

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	76	-11%	-4%
2	77	-9%	7%
3	69	-3%	14%
4	76	7%	13%
5	83	10%	7%
6	85	8%	-3%
7	73	4%	-15%
8	86	-3%	-8%
9	81	-8%	-6%
10	80	-10%	2%
11	77	-7%	12%
12	80	3%	8%
13	87	7%	-2%
14	82	7%	-11%
15	76	2%	-13%
16	79	-8%	-13%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1822lx	456lx	202lx	114lx	73lx	51lx	37lx	28lx	22lx	18lx	15lx	13lx	11lx	9lx	8lx	7lx	6lx	6lx	5lx	5lx
169.3fcd	42.3fcd	18.8fcd	10.6fcd	6.8fcd	4.7fcd	3.5fcd	2.6fcd	2.1fcd	1.7fcd	1.4fcd	1.2fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.5fcd	0.5fcd	0.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1822	1821	1811	1794	1770	1741	1704	1662	1614	1562	1506	1446	1382	1315	1248	1177	1099	991	858	712
100%	100%	99%	98%	97%	96%	94%	91%	89%	86%	83%	79%	76%	72%	68%	65%	60%	54%	47%	39%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1822	1821	1811	1794	1770	1741	1704	1662	1614	1562	1506	1446	1382	1315	1248	1177	1099	991	858	712
100%	100%	99%	98%	97%	96%	94%	91%	89%	86%	83%	79%	76%	72%	68%	65%	60%	54%	47%	39%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1822	1821	1811	1794	1770	1741	1704	1662	1614	1562	1506	1446	1382	1315	1248	1177	1099	991	858	712
100%	100%	99%	98%	97%	96%	94%	91%	89%	86%	83%	79%	76%	72%	68%	65%	60%	54%	47%	39%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1822	1821	1811	1794	1770	1741	1704	1662	1614	1562	1506	1446	1382	1315	1248	1177	1099	991	858	712
100%	100%	99%	98%	97%	96%	94%	91%	89%	86%	83%	79%	76%	72%	68%	65%	60%	54%	47%	39%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
70.5°	94.7°	137.2°	95.5%	88.3%