

Light efficiency:

92 Lumen/Watt

Light quality:

CRI: 84.3

Color temperature:

3057 K

Output: 2118 lm

Peak: 1881 cd

Power: 23.0 W

PF: 0.98




Product name:

**NU3-QD-SW-27LM-30K-80-D70-120-DIM10-NC-WH-WH**

Date and time:

**12/19/2018 6:53:02 AM**




Beam angle

**68.3°**






CIE 1931  
x: 0.435  
y: 0.407

Spectra




Power







**TM30: 84.8**



**CRI: 84.3 (R1-R8)**



**CQS: 84.0**



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.0	92.7	96.0	82.7	83.4	91.8	83.5	61.0	11.6	83.6	83.0	74.3	85.5	98.4	74.5

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
78.4	81.5	81.0	91.9	92.4	94.5	87.2	92.2	87.4	80.6	82.8	86.0	86.3	78.2	77.8	75.5

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
78.7	94.3	86.4	82.8	84.7	85.4	85.7	88.8	95.0	92.5	89.3	86.3	84.3	72.6	74.8

## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3057 K	84.3	11.6	84.8	94.7	84.0	0.435	0.407	0.248	0.348	0.0013







**Rf 84.8**

Fidelity index Rf


**Rg 94.7**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	78	-11%	1%
2	81	-7%	6%
3	81	-3%	8%
4	92	-1%	4%
5	92	-2%	2%
6	94	0%	-2%
7	87	-6%	-3%
8	92	-4%	1%
9	87	-5%	6%
10	81	-3%	10%
11	83	1%	10%
12	86	7%	-1%
13	86	3%	-9%
14	78	3%	-16%
15	78	-4%	-12%
16	76	-8%	-15%



## Beam Details



### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1875lx	469lx	208lx	117lx	75lx	52lx	38lx	29lx	23lx	19lx	15lx	13lx	11lx	10lx	8lx	7lx	6lx	6lx	5lx	5lx
174.2fcd	43.5fcd	19.4fcd	10.9fcd	7fcd	4.8fcd	3.6fcd	2.7fcd	2.2fcd	1.7fcd	1.4fcd	1.2fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.5fcd	0.5fcd	0.4fcd

### Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1875	1861	1861	1844	1817	1787	1744	1701	1646	1589	1528	1461	1393	1323	1251	1172	1082	990	813	636
100%	99%	99%	98%	97%	95%	93%	91%	88%	85%	82%	78%	74%	71%	67%	62%	58%	53%	43%	34%

### Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1875	1872	1867	1845	1822	1787	1750	1706	1652	1598	1533	1468	1398	1326	1252	1168	1084	957	803	648
100%	100%	100%	98%	97%	95%	93%	91%	88%	85%	82%	78%	75%	71%	67%	62%	58%	51%	43%	35%

### Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1875	1861	1861	1844	1817	1787	1744	1701	1646	1589	1528	1461	1393	1323	1251	1172	1082	990	813	636
100%	99%	99%	98%	97%	95%	93%	91%	88%	85%	82%	78%	74%	71%	67%	62%	58%	53%	43%	34%

### Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1875	1872	1867	1845	1822	1787	1750	1706	1652	1598	1533	1468	1398	1326	1252	1168	1084	957	803	648
100%	100%	100%	98%	97%	95%	93%	91%	88%	85%	82%	78%	75%	71%	67%	62%	58%	51%	43%	35%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
68.3°	90°	130.6°	96.0%	89.7%