

Light efficiency:

77 Lumen/Watt

Light quality:

CRI: 82.7

Color temperature:

2966 K

Output: 1257 lm

Peak: 897 cd


Power: 16.4 W

PF: 0.96



NU3-RW-SW-20LM-30K-80-WW-120-DIM10-NC-WH-WH

Date and time:
2/22/2021 10:23:06 AM




Beam angle

68.8°






CIE 1931
x: 0.443
y: 0.411

Spectra




Power







TM30: 85.8



CRI: 82.7 (R1-R8)



CQS: 82.7



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
80.7	90.5	97.0	81.6	81.0	89.2	83.1	58.3	4.5	79.0	81.6	72.6	82.9	98.9	71.7

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.7	81.7	79.8	90.2	94.3	94.1	87.6	93.9	89.5	85.6	83.9	86.3	87.9	80.3	83.6	76.4

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
76.9	94.7	85.1	82.5	84.2	84.2	84.3	87.8	95.1	90.9	88.0	85.0	83.1	70.1	72.5

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2966 K	82.7	4.5	85.8	95.3	82.7	0.443	0.411	0.251	0.350	0.0020







Rf 85.8


Fidelity index Rf

Rg 95.3

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	80	-11%	-1%
2	82	-8%	6%
3	80	-4%	10%
4	90	0%	6%
5	94	2%	4%
6	94	2%	-2%
7	88	-4%	-7%
8	94	-3%	-1%
9	90	-6%	2%
10	86	-4%	8%
11	84	-1%	11%
12	86	6%	2%
13	88	4%	-8%
14	80	4%	-16%
15	84	-3%	-10%
16	76	-9%	-16%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
791lx	198lx	88lx	49lx	32lx	22lx	16lx	12lx	10lx	8lx	7lx	5lx	5lx	4lx	4lx	3lx	3lx	2lx	2lx	2lx
73.5fcd	18.4fcd	8.2fcd	4.6fcd	2.9fcd	2fcd	1.5fcd	1.1fcd	0.9fcd	0.7fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd	0.3fcd	0.2fcd	0.2fcd	0.2fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
791	812	877	896	869	798	695	576	451	336	235	150	86	54	40	35	37	43	46	38
100%	103%	111%	113%	110%	101%	88%	73%	57%	42%	30%	19%	11%	7%	5%	4%	5%	5%	6%	5%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
791	812	797	773	740	698	646	584	509	412	303	200	118	65	36	19	10	5	2	1
100%	103%	101%	98%	93%	88%	82%	74%	64%	52%	38%	25%	15%	8%	5%	2%	1%	1%	0%	0%

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
791	606	488	370	267	186	131	97	77	61	49	39	28	19	10	7	3	0	0	0
100%	77%	62%	47%	34%	24%	17%	12%	10%	8%	6%	5%	4%	2%	1%	1%	0%	0%	0%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
791	812	797	773	740	698	646	584	509	412	303	200	118	65	36	19	10	5	2	1
100%	103%	101%	98%	93%	88%	82%	74%	64%	52%	38%	25%	15%	8%	5%	2%	1%	1%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
{B_ANG}°	112.3°	154.3°	92.2%	74.2%