

Light efficiency:

**104 Lumen/Watt**

Light quality:

**CRI: 84.9**

Color temperature:

**3042 K**

**Output: 1702 lm**

**Peak: 943 cd**

**Power: 16.3 W**

**PF: 0.97**




Product name:

**NU4-QW-SW-20LM-30K-80-WW-120-DIM10-NC-WH-WH**

Date and time:

**6/6/2019 3:52:21 PM**




Beam angle

**82.8°**






CIE 1931  
x: 0.436  
y: 0.407

Spectra




Power






TM30: 85.4



CRI: 84.9 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.7	92.7	96.6	83.9	84.1	91.9	84.2	62.2	14.0	83.7	84.6	74.7	86.0	98.7	75.2


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.3	82.2	81.2	92.0	92.7	94.7	88.0	93.6	88.8	82.3	83.1	85.6	86.6	78.6	78.4	76.1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
79.1	94.5	86.5	83.8	85.9	86.5	86.5	89.1	95.2	92.5	89.7	86.9	85.0	73.3	75.4

CQS: 84.6



## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3042 K	84.9	14.0	85.4	95.4	84.6	0.436	0.407	0.249	0.348	0.0014

## TM30 Details







**Rf 85.4**


Fidelity index Rf

**Rg 95.4**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	79	-10%	0%
2	82	-7%	5%
3	81	-3%	8%
4	92	-1%	4%
5	93	-2%	2%
6	95	0%	-2%
7	88	-5%	-4%
8	94	-3%	1%
9	89	-5%	5%
10	82	-3%	8%
11	83	1%	11%
12	86	6%	1%
13	87	3%	-8%
14	79	4%	-15%
15	78	-4%	-12%
16	76	-8%	-15%





### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
670lx	167lx	74lx	42lx	27lx	19lx	14lx	10lx	8lx	7lx	6lx	5lx	4lx	3lx	3lx	3lx	2lx	2lx	2lx	2lx
62.2fcd	15.6fcd	6.9fcd	3.9fcd	2.5fcd	1.7fcd	1.3fcd	1fcd	0.8fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd	0.2fcd	0.2fcd	0.2fcd	0.2fcd	0.2fcd

### Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
670	663	655	647	636	621	598	566	522	458	379	293	196	110	65	47	27	12	0	0
100%	99%	98%	97%	95%	93%	89%	85%	78%	68%	57%	44%	29%	16%	10%	7%	4%	2%	0%	0%

### Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
670	601	531	465	411	366	324	285	253	217	176	132	97	76	59	40	20	9	0	0
100%	90%	79%	69%	61%	55%	48%	43%	38%	32%	26%	20%	14%	11%	9%	6%	3%	1%	0%	0%

### Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
670	677	682	686	686	677	656	620	563	483	386	279	167	88	53	33	15	4	2	0
100%	101%	102%	102%	102%	101%	98%	93%	84%	72%	58%	42%	25%	13%	8%	5%	2%	1%	0%	0%

### Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
670	737	796	846	876	879	848	790	702	580	442	306	168	72	36	20	7	2	1	0
100%	110%	119%	126%	131%	131%	127%	118%	105%	87%	66%	46%	25%	11%	5%	3%	1%	0%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
82.8°	132.6°	157.4°	90.2%	64.6%