

Light efficiency:

83 Lumen/Watt

Light quality:

CRI: 84.6

Color temperature:

3020 K

Output: 2185 lm

Peak: 2389 cd

Power: 26.4 W

PF: 0.98




Product name:

NU4-RD-SW-30LM-30K-80-D60-120-DIM10-NC-WH-WH

Date and time:

8/3/2018 12:05:08 PM




Beam angle

61.4°




CIE 1931
x: 0.439
y: 0.410



Spectra




Power




Color details



TM30: 85.5



CRI: 84.6 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.2	92.2	96.8	83.7	83.6	91.6	84.2	61.6	12.4	82.8	84.3	74.8	85.4	98.8	74.4


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.0	82.0	81.3	92.1	93.0	94.9	88.0	93.5	88.9	82.7	83.5	85.8	86.6	78.6	78.2	76.3

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
78.8	94.4	87.0	84.2	85.9	86.3	86.3	89.5	95.1	92.7	89.9	87.1	85.0	72.7	75.0

CQS: 84.5



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3020 K	84.6	12.4	85.5	95.1	84.5	0.439	0.410	0.249	0.349	0.0020

TM30 details







Rf 85.5

Fidelity index Rf


Rg 95.1

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	79	-10%	0%
2	82	-7%	5%
3	81	-3%	8%
4	92	-1%	4%
5	93	-2%	2%
6	95	0%	-1%
7	88	-5%	-4%
8	93	-3%	1%
9	89	-5%	5%
10	83	-3%	8%
11	84	1%	11%
12	86	6%	1%
13	87	3%	-8%
14	79	3%	-16%
15	78	-4%	-12%
16	76	-8%	-14%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2389lx	597lx	265lx	149lx	96lx	66lx	49lx	37lx	29lx	24lx	20lx	17lx	14lx	12lx	11lx	9lx	8lx	7lx	7lx	6lx
222fcd	55.5fcd	24.7fcd	13.9fcd	8.9fcd	6.2fcd	4.5fcd	3.5fcd	2.7fcd	2.2fcd	1.8fcd	1.5fcd	1.3fcd	1.1fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2389	2382	2361	2327	2278	2217	2146	2067	1984	1904	1826	1747	1666	1576	1455	1274	1045	808	588	410
100%	100%	99%	97%	95%	93%	90%	87%	83%	80%	76%	73%	70%	66%	61%	53%	44%	34%	25%	17%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2389	2382	2361	2327	2278	2217	2146	2067	1984	1904	1826	1747	1666	1576	1455	1274	1045	808	588	410
100%	100%	99%	97%	95%	93%	90%	87%	83%	80%	76%	73%	70%	66%	61%	53%	44%	34%	25%	17%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2389	2382	2361	2327	2278	2217	2146	2067	1984	1904	1826	1747	1666	1576	1455	1274	1045	808	588	410
100%	100%	99%	97%	95%	93%	90%	87%	83%	80%	76%	73%	70%	66%	61%	53%	44%	34%	25%	17%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2389	2382	2361	2327	2278	2217	2146	2067	1984	1904	1826	1747	1666	1576	1455	1274	1045	808	588	410
100%	100%	99%	97%	95%	93%	90%	87%	83%	80%	76%	73%	70%	66%	61%	53%	44%	34%	25%	17%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
61.4°	83°	110.2°	98.2%	93.4%