

Light efficiency:

94 Lumen/Watt

Light quality:

CRI: 82.6

Color temperature:

2948 K

Output: 1143 lm

Peak: 9560 cd


Power: 12.2 W

PF: 0.95




NU4-RD-SW-15LM-30K-80-S10-120-DIM10-NC-WH-WH

Date and time:
2/27/2021 10:42:26 AM






CIE 1931
x: 0.443
y: 0.409

Spectra




Power






TM30: 83.7



CRI: 82.6 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.1	88.5	95.5	82.9	80.7	85.8	84.8	61.8	10.6	73.8	82.8	69.0	82.4	97.2	73.2


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
80.8	81.5	75.7	83.8	88.2	88.5	81.7	90.9	88.0	85.8	81.4	84.1	88.1	82.2	82.0	78.9

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
75.9	96.2	81.9	81.1	82.5	80.7	82.1	86.3	96.2	87.7	86.0	84.3	83.5	71.5	72.9

CQS: 81.8



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2948 K	82.6	10.6	83.7	98.6	81.8	0.443	0.409	0.252	0.349	0.0012







Rf 83.7


Fidelity index Rf

Rg 98.6

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	81	-11%	-3%
2	81	-8%	7%
3	76	-3%	13%
4	84	4%	10%
5	88	8%	6%
6	88	7%	-3%
7	82	2%	-12%
8	91	-2%	-5%
9	88	-6%	-3%
10	86	-7%	4%
11	81	-4%	12%
12	84	5%	6%
13	88	7%	-4%
14	82	7%	-13%
15	82	1%	-11%
16	79	-7%	-15%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
9560lx	2390lx	1062lx	598lx	382lx	266lx	195lx	149lx	118lx	96lx	79lx	66lx	57lx	49lx	42lx	37lx	33lx	30lx	26lx	24lx
888.2fcd	222fcd	98.7fcd	55.5fcd	35.5fcd	24.7fcd	18.1fcd	13.9fcd	11fcd	8.9fcd	7.3fcd	6.2fcd	5.3fcd	4.5fcd	3.9fcd	3.5fcd	3.1fcd	2.7fcd	2.5fcd	2.2fcd

Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9560	9560	9012	8237	7404	6416	5428	4532	3655	2882	2269	1656	1348	1056	860	755	656	622	588	568
100%	100%	94%	86%	77%	67%	57%	47%	38%	30%	24%	17%	14%	11%	9%	8%	7%	7%	6%	6%

Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9560	9560	9012	8237	7404	6416	5428	4532	3655	2882	2269	1656	1348	1056	860	755	656	622	588	568
100%	100%	94%	86%	77%	67%	57%	47%	38%	30%	24%	17%	14%	11%	9%	8%	7%	7%	6%	6%

Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9560	9560	9012	8237	7404	6416	5428	4532	3655	2882	2269	1656	1348	1056	860	755	656	622	588	568
100%	100%	94%	86%	77%	67%	57%	47%	38%	30%	24%	17%	14%	11%	9%	8%	7%	7%	6%	6%

Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
9560	9560	9012	8237	7404	6416	5428	4532	3655	2882	2269	1656	1348	1056	860	755	656	622	588	568
100%	100%	94%	86%	77%	67%	57%	47%	38%	30%	24%	17%	14%	11%	9%	8%	7%	7%	6%	6%

Beam angle 50°	Field angle 10°	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
{B_ANG}°	26.7°	70.7°	99.2%	97.4%