

Light efficiency:

58 Lumen/Watt

Light quality:

CRI: 96.0

Color temperature:

3129 K

Output: 1516 lm

Peak: 4559 cd

Power: 26.3 W

PF: 0.98




Product name:

NU4-RD-WD-20LM-3018-97-
SS25-120-DIM10-NC-WH-WH


Date and time:

6/13/2018 12:00:40 PM




CIE 1931
x: 0.432
y: 0.410



Spectra




Power




Color details



TM30: 92.7



CRI: 96.0 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97.0	96.3	93.9	98.0	95.5	95.0	98.6	93.7	82.0	89.7	98.0	77.4	96.7	95.6	94.5


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
94.1	96.2	94.9	93.8	92.2	96.7	93.4	97.3	93.1	87.5	87.6	91.2	94.9	91.2	91.2	87.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
92.8	96.9	90.6	90.9	93.8	95.0	95.6	97.4	96.0	94.1	94.0	95.0	96.2	93.9	94.0

CQS: 94.0



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3129 K	96.0	82.0	92.7	99.4	94.0	0.432	0.410	0.245	0.349	0.0030

TM30 details







Rf 92.7

Fidelity index Rf


Rg 99.4

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	94	-2%	0%
2	96	-2%	0%
3	95	-1%	1%
4	94	-3%	0%
5	92	-4%	2%
6	97	0%	1%
7	93	-3%	2%
8	97	-1%	1%
9	93	-1%	4%
10	88	-1%	7%
11	88	2%	8%
12	91	5%	1%
13	95	2%	-2%
14	91	4%	-4%
15	91	0%	-3%
16	88	1%	-9%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
4559lx	1140lx	507lx	285lx	182lx	127lx	93lx	71lx	56lx	46lx	38lx	32lx	27lx	23lx	20lx	18lx	16lx	14lx	13lx	11lx
423.6fcd	105.9fcd	47.1fcd	26.5fcd	16.9fcd	11.8fcd	8.6fcd	6.6fcd	5.2fcd	4.2fcd	3.5fcd	2.9fcd	2.5fcd	2.2fcd	1.9fcd	1.7fcd	1.5fcd	1.3fcd	1.2fcd	1.1fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
4559	4456	4209	3819	3336	2850	2411	2031	1709	1440	1218	1036	886	769	683	611	507	383	256	147
100%	98%	92%	84%	73%	63%	53%	45%	37%	32%	27%	23%	19%	17%	15%	13%	11%	8%	6%	3%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
4559	4456	4209	3819	3336	2850	2411	2031	1709	1440	1218	1036	886	769	683	611	507	383	256	147
100%	98%	92%	84%	73%	63%	53%	45%	37%	32%	27%	23%	19%	17%	15%	13%	11%	8%	6%	3%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
4559	4456	4209	3819	3336	2850	2411	2031	1709	1440	1218	1036	886	769	683	611	507	383	256	147
100%	98%	92%	84%	73%	63%	53%	45%	37%	32%	27%	23%	19%	17%	15%	13%	11%	8%	6%	3%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
4559	4456	4209	3819	3336	2850	2411	2031	1709	1440	1218	1036	886	769	683	611	507	383	256	147
100%	98%	92%	84%	73%	63%	53%	45%	37%	32%	27%	23%	19%	17%	15%	13%	11%	8%	6%	3%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
25.2°	65.8°	77.9°	99.0%	96.8%