

BETA

6" Round Architectural Cylinder High Performance



DESCRIPTION

- The BETA6RX is an economical and highly efficient spec grade 6" cylinder with thoughtful construction and pleasing aesthetics. Static White provides premium performance using efficient chip-on-board (COB) LED technology. Standard with premium dimming using 1% flicker free drivers in 120V-277V universal voltage. Beam spread and finishes allow for creative lighting solutions to illuminate architectural spaces. 6" to 10' field adjustable stem. BETA6RX carries a 5-Year Warranty.

HOUSING

- 6" extruded aluminum housing with black, white or matte chrome finish

MOUNTING

- Easy mounting system over a 3-1/2" to 4" recessed octagonal junction box for rigid pendant mounting option.
- RP mounting option can be mounted on $\leq 45^\circ$ sloped ceiling. Consult factory for custom pendant lengths.

LISTING

- ULus Listed to UL1598 (suitable for dry and damp locations)
- UL Listed to CSA C22.2 #250.0

LED INFO

- Bridgelux BXRC:
80 CRI: SDCM = 3-step MacAdam Ellipse, Lumen Maintenance: $L_{70} > 50,000$ hrs
- Bridgelux BXRC:
90 CRI: SDCM = 2-step MacAdam Ellipse, Lumen Maintenance: $L_{70} > 50,000$ hrs

PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

STANDARD COB - ORDERING CODE

SERIES	BETA																
TYPE	6RX	6" round high output															
LED	SW	standard white															
DELIVERED LUMENS	60LM 70LM 80LM 90LM 100LM ²	5260 lm 6190 lm 7500 lm 8845 lm 9930 lm <small>Calculated Delivered Lumens = [Delivered Lumen Value] x [CCT Multiplier] Standard Configuration: 3000K 80CRI 40D</small>															
CCT	27K 30K 35K 40K	<table border="1"> <thead> <tr> <th>CCT</th> <th>2700K</th> <th>3000K</th> <th>3500K</th> <th>4000K</th> </tr> </thead> <tbody> <tr> <td>CRI</td> <td>80+</td> <td>90+</td> <td>80+</td> <td>90+</td> </tr> <tr> <td>CCT MULTIPLIER FOR LUMEN OUTPUT</td> <td>0.94</td> <td>0.8</td> <td>1</td> <td>0.81</td> </tr> </tbody> </table>	CCT	2700K	3000K	3500K	4000K	CRI	80+	90+	80+	90+	CCT MULTIPLIER FOR LUMEN OUTPUT	0.94	0.8	1	0.81
CCT	2700K	3000K	3500K	4000K													
CRI	80+	90+	80+	90+													
CCT MULTIPLIER FOR LUMEN OUTPUT	0.94	0.8	1	0.81													
CRI	80 90	80 CRI 90 CRI															
REFLECTOR	25C ² 35C ² 40C ² 70C ² 25NL 35NL 40NL 70NL	25° reflector with clear lens (0.96) 35° reflector with clear lens (0.96) 40° reflector with clear lens (0.97) 70° reflector with clear lens (0.93) 25° reflector with no lens (0.99) 35° reflector with no lens (0.99) 40° reflector with no lens (1.00) 70° reflector with no lens (0.96)															
VOLTAGE	UNV	120V-277V															
DIMMING	DIM10 DIM10Z DALI DALIZ DMXZ ³ CAS	eldoLED flicker free 0-10V dimming to 1% eldoLED flicker free 0-10V dimming to 0% eldoLED flicker free DALI dimming to 1% eldoLED flicker free DALI dimming to 0% DMX dim to 0.1% (DMX512-A/RDM) Casambi Bluetooth control with flicker free 1% dimming															
MOUNTING OPTIONS	RP RP5 RP6 RP8 RP10	rigid pendant with swivel canopy rigid pendant 5' stem with swivel stem/canopy rigid pendant 6' stem with swivel stem/canopy rigid pendant 8' stem with swivel stem/canopy rigid pendant 10' stem with swivel stem/canopy															
FINISH	BK WH MC	black white matte chrome															

ORDERING CODE

Follow the steps to specify your fixture, example:
BETA - 6RX - SW - 100LM - 35K - 90 - 40D - UNV - DIM10 - RP - WH

SW (LED)	POWER
DELIVERED LM	W (80/90 CRI)
9930	90
8845	75
7500	61
6190	49
5260	40

Power Factor ≥ 0.9

NOTES


1. Ambient temperature = 40C max. For higher temperatures consult factory.
2. Clear Lens option not available in 100LM
3. Logarithmic dimming curve as standard for linear or square, add LIN or SQU after dimming code, i.e. DMXZLIN

alphabet


PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

MOUNTING OPTIONS

BETA6RX



- H 49-3/8" (field adjustable to 6")
- RP 61-3/8" (field adjustable to 6")
- RP5 73-3/8" (field adjustable to 6")
- RP8 97-3/8" (field adjustable to 54")
- RP10 121-3/8" (field adjustable to 66")



RP
Rigid Pendant