

Light efficiency:

47 Lumen/Watt

Light quality:

CRI: 90.4

Color temperature:

2997 K

Output: 812 lm

Peak: 19151 cd

Power: 17.4 W


PF: 0.97



NU3-RA-SW-10LM-30K-90-9D-NA-NL-WH


Date and time:

5/31/2022 2:40:00 PM






CIE 1931  
x: 0.440  
y: 0.410

Spectra




Power






TM30: 90.7



CRI: 90.4 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
90.2	92.8	94.7	92.0	89.6	91.3	92.4	80.3	52.4	82.8	92.7	80.6	90.5	96.4	85.5


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
89.6	90.6	86.9	90.5	92.2	92.6	89.1	94.6	93.1	92.0	89.6	90.2	92.7	90.0	88.1	89.1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
85.6	97.0	88.9	89.0	89.4	88.0	89.6	92.8	96.9	92.2	91.9	91.7	91.5	84.2	84.6

CQS: 89.4



## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2997 K	90.4	52.4	90.7	100.1	89.4	0.440	0.410	0.250	0.349	0.0019







**Rf 90.7**


Fidelity index Rf

**Rg 100.1**

Gammut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	90	-5%	-2%
2	91	-4%	3%
3	87	-2%	7%
4	91	3%	6%
5	92	5%	4%
6	93	5%	-1%
7	89	2%	-7%
8	95	0%	-4%
9	93	-3%	-2%
10	92	-4%	2%
11	90	-3%	7%
12	90	3%	3%
13	93	4%	-2%
14	90	4%	-7%
15	88	1%	-8%
16	89	-3%	-8%





#### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
19146lx	4787lx	2127lx	1197lx	766lx	532lx	391lx	299lx	236lx	191lx	158lx	133lx	113lx	98lx	85lx	75lx	66lx	59lx	53lx	48lx
1778.7fcd	444.7fcd	197.6fcd	111.2fcd	71.1fcd	49.4fcd	36.3fcd	27.8fcd	22fcd	17.8fcd	14.7fcd	12.4fcd	10.5fcd	9.1fcd	7.9fcd	6.9fcd	6.2fcd	5.5fcd	4.9fcd	4.4fcd

#### Intensities in 0° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
19.1K	18.6K	16.9K	14.6K	11.9K	9.3K	6.9K	5.0K	3.5K	2.5K	1.7K	1.2K	0.9K	0.7K	0.6K	0.4K	0.4K	0.3K	0.2K	0.2K
100%	97%	88%	76%	62%	48%	36%	26%	19%	13%	9%	6%	5%	4%	3%	2%	2%	1%	1%	1%

#### Intensities in 90° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
19.1K	18.6K	17.0K	14.6K	11.8K	9.1K	6.7K	4.7K	3.3K	2.3K	1.6K	1.1K	0.8K	0.6K	0.5K	0.4K	0.3K	0.2K	0.2K	0.1K
100%	97%	89%	76%	62%	47%	35%	25%	17%	12%	8%	6%	4%	3%	2%	2%	1%	1%	1%	1%

#### Intensities in 180° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
19.1K	18.6K	16.9K	14.6K	11.9K	9.3K	6.9K	5.0K	3.5K	2.5K	1.7K	1.2K	0.9K	0.7K	0.6K	0.4K	0.4K	0.3K	0.2K	0.2K
100%	97%	88%	76%	62%	48%	36%	26%	19%	13%	9%	6%	5%	4%	3%	2%	2%	1%	1%	1%

#### Intensities in 270° c-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
19.1K	18.6K	17.0K	14.6K	11.8K	9.1K	6.7K	4.7K	3.3K	2.3K	1.6K	1.1K	0.8K	0.6K	0.5K	0.4K	0.3K	0.2K	0.2K	0.1K
100%	97%	89%	76%	62%	47%	35%	25%	17%	12%	8%	6%	4%	3%	2%	2%	1%	1%	1%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
9.7°	19.3°	29°	99.5%	99.4%