

Light efficiency:

53 Lumen/Watt

Light quality:

CRI: 93.1

Color temperature:

3012 K

Output: 813 lm

Peak: 2155 cd


Power: 15.5 W

PF: 0.97




NU4-RD-TW-10LM-2765-95-35D-HCL-WH-WH

Date and time:
3/30/2023 4:29:03 PM






CIE 1931
x: 0.434
y: 0.399

Spectra




Power






TM30: 90.2



CRI: 93.1 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
94.9	99.4	96.6	92.4	94.5	95.9	89.8	81.6	62.2	98.0	93.8	81.0	96.7	99.1	90.8


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
89.2	92.4	93.3	93.0	92.4	95.4	89.2	93.8	88.8	86.0	88.1	90.0	89.8	86.8	86.9	84.9

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
87.3	94.5	91.0	87.8	89.2	91.2	93.4	93.0	96.5	96.3	94.2	92.7	92.0	87.7	87.7

CQS: 91.0



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3012 K	93.1	62.2	90.2	97.1	91.0	0.434	0.399	0.251	0.346	-0.0018







Rf 90.2


Fidelity index Rf

Rg 97.1

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	89	-5%	2%
2	92	-3%	2%
3	93	-1%	3%
4	93	-3%	-1%
5	92	-6%	0%
6	95	-2%	0%
7	89	-6%	3%
8	94	-2%	3%
9	89	-1%	7%
10	86	1%	9%
11	88	4%	8%
12	90	6%	-2%
13	90	1%	-8%
14	87	2%	-10%
15	87	-3%	-5%
16	85	-3%	-11%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2153lx	538lx	239lx	135lx	86lx	60lx	44lx	34lx	27lx	22lx	18lx	15lx	13lx	11lx	10lx	8lx	7lx	7lx	6lx	5lx
200fcd	50fcd	22.2fcd	12.5fcd	8fcd	5.6fcd	4.1fcd	3.1fcd	2.5fcd	2fcd	1.7fcd	1.4fcd	1.2fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2153	2106	2011	1880	1740	1576	1407	1238	1067	906	765	632	534	443	382	308	237	165	105	58
100%	98%	93%	87%	81%	73%	65%	58%	50%	42%	36%	29%	25%	21%	18%	14%	11%	8%	5%	3%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2153	2112	2007	1873	1711	1545	1374	1206	1043	875	738	615	511	429	363	305	238	168	104	55
100%	98%	93%	87%	79%	72%	64%	56%	48%	41%	34%	29%	24%	20%	17%	14%	11%	8%	5%	3%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2153	2106	2011	1880	1740	1576	1407	1238	1067	906	765	632	534	443	382	308	237	165	105	58
100%	98%	93%	87%	81%	73%	65%	58%	50%	42%	36%	29%	25%	21%	18%	14%	11%	8%	5%	3%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2153	2112	2007	1873	1711	1545	1374	1206	1043	875	738	615	511	429	363	305	238	168	104	55
100%	98%	93%	87%	79%	72%	64%	56%	48%	41%	34%	29%	24%	20%	17%	14%	11%	8%	5%	3%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
31.3°	65.1°	76.3°	98.9%	98.2%