

Light efficiency:

82 Lumen/Watt

Light quality:

CRI: 84.1

Color temperature:

3071 K

Output: 2771 lm

Peak: 14720 cd


Power: 33.9 W

PF: 0.98




NU4-RD-TW-30LM-2750-80-15D-HET-WH-WH

Date and time:
4/3/2023 11:32:52 AM






CIE 1931
x: 0.429
y: 0.395

Spectra




Power






TM30: 84.5



CRI: 84.1 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.1	91.2	96.5	83.1	83.0	88.8	84.0	62.9	15.0	79.4	83.1	71.3	85.1	98.4	76.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
81.8	82.0	76.4	85.9	90.9	90.1	86.2	92.8	90.3	83.0	79.6	85.8	88.4	81.5	80.3	78.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
78.8	96.5	79.9	78.9	83.3	83.4	82.4	85.3	96.4	87.7	84.7	82.5	82.5	73.2	74.8

CQS: 82.1



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3071 K	84.1	15.0	84.5	98.7	82.1	0.429	0.395	0.249	0.345	-0.0024







Rf 84.5


Fidelity index Rf

Rg 98.7

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	82	-10%	-1%
2	82	-8%	7%
3	76	-2%	12%
4	86	3%	9%
5	91	4%	5%
6	90	6%	-2%
7	86	-1%	-8%
8	93	-2%	-4%
9	90	-6%	1%
10	83	-5%	8%
11	80	-1%	14%
12	86	8%	4%
13	88	6%	-4%
14	81	7%	-13%
15	80	0%	-13%
16	79	-6%	-16%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
14707lx	3677lx	1634lx	919lx	588lx	409lx	300lx	230lx	182lx	147lx	122lx	102lx	87lx	75lx	65lx	57lx	51lx	45lx	41lx	37lx
1366.4fcd	341.6fcd	151.8fcd	85.4fcd	54.7fcd	38fcd	27.9fcd	21.3fcd	16.9fcd	13.7fcd	11.3fcd	9.5fcd	8.1fcd	7fcd	6.1fcd	5.3fcd	4.7fcd	4.2fcd	3.8fcd	3.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
14.7K	14.1K	12.8K	10.8K	8.7K	6.7K	5.1K	3.8K	2.9K	2.2K	1.7K	1.4K	1.2K	1.0K	0.9K	0.8K	0.7K	0.6K	0.5K	0.4K
100%	96%	87%	74%	59%	46%	35%	26%	20%	15%	12%	10%	8%	7%	6%	5%	5%	4%	3%	3%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
14.7K	14.2K	12.8K	10.8K	8.6K	6.5K	4.8K	3.5K	2.6K	1.9K	1.5K	1.3K	1.1K	1.0K	0.8K	0.8K	0.7K	0.5K	0.4K	0.3K
100%	97%	87%	74%	59%	44%	33%	24%	17%	13%	10%	9%	7%	6%	6%	5%	4%	4%	3%	2%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
14.7K	14.3K	13.1K	11.1K	8.8K	6.7K	4.9K	3.5K	2.5K	1.9K	1.5K	1.2K	1.0K	0.9K	0.8K	0.7K	0.6K	0.5K	0.4K	0.3K
100%	97%	89%	75%	60%	45%	33%	24%	17%	13%	10%	8%	7%	6%	6%	5%	4%	4%	3%	2%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
14.7K	14.2K	12.9K	10.9K	8.6K	6.5K	4.8K	3.5K	2.6K	1.9K	1.5K	1.3K	1.1K	1.0K	0.9K	0.8K	0.7K	0.6K	0.4K	0.3K
100%	97%	87%	74%	58%	44%	33%	24%	17%	13%	10%	9%	7%	7%	6%	5%	5%	4%	3%	2%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
18.5°	41.2°	75°	99.6%	97.8%