

Light efficiency:

56 Lumen/Watt

Light quality:

CRI: 93.3

Color temperature:

2982 K

Output: 1374 lm

Peak: 3401 cd


Power: 24.4 W

PF: 0.98




NU4-RD-TW-20LM-2765-95-40D-HCL-WH-WH

Date and time:
3/28/2023 9:03:57 AM






CIE 1931
x: 0.436
y: 0.399

Spectra




Power






TM30: 91.0



CRI: 93.3 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
94.7	99.0	97.2	92.8	94.5	96.3	90.2	81.7	61.7	96.8	94.1	82.4	96.3	99.5	90.6


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
89.8	92.4	92.5	92.9	95.0	96.3	91.3	95.3	90.6	87.4	88.7	90.1	90.4	87.2	90.9	84.5

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
88.0	94.9	90.5	88.0	90.2	92.4	93.1	92.6	96.7	95.6	93.7	92.3	91.8	87.6	87.7

CQS: 91.1



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2982 K	93.3	61.7	91.0	97.7	91.1	0.436	0.399	0.252	0.346	-0.0019







Rf 91.0


Fidelity index Rf

Rg 97.7

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	90	-5%	1%
2	92	-3%	3%
3	92	-1%	3%
4	93	-3%	-1%
5	95	-3%	1%
6	96	-1%	0%
7	91	-5%	1%
8	95	-2%	2%
9	91	-1%	6%
10	87	1%	8%
11	89	4%	8%
12	90	5%	-1%
13	90	2%	-7%
14	87	3%	-10%
15	91	-4%	-3%
16	85	-3%	-11%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
3396lx	849lx	377lx	212lx	136lx	94lx	69lx	53lx	42lx	34lx	28lx	24lx	20lx	17lx	15lx	13lx	12lx	10lx	9lx	8lx
315.5fcd	78.9fcd	35.1fcd	19.7fcd	12.6fcd	8.8fcd	6.4fcd	4.9fcd	3.9fcd	3.2fcd	2.6fcd	2.2fcd	1.9fcd	1.6fcd	1.4fcd	1.2fcd	1.1fcd	1fcd	0.9fcd	0.8fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3396	3338	3203	3005	2779	2544	2284	2015	1758	1501	1271	1066	888	749	630	521	399	285	186	109
100%	98%	94%	88%	82%	75%	67%	59%	52%	44%	37%	31%	26%	22%	19%	15%	12%	8%	5%	3%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3396	3343	3202	3017	2808	2572	2324	2056	1802	1550	1313	1106	919	775	651	526	398	287	190	112
100%	98%	94%	89%	83%	76%	68%	61%	53%	46%	39%	33%	27%	23%	19%	15%	12%	8%	6%	3%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3396	3338	3203	3005	2779	2544	2284	2015	1758	1501	1271	1066	888	749	630	521	399	285	186	109
100%	98%	94%	88%	82%	75%	67%	59%	52%	44%	37%	31%	26%	22%	19%	15%	12%	8%	5%	3%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3396	3343	3202	3017	2808	2572	2324	2056	1802	1550	1313	1106	919	775	651	526	398	287	190	112
100%	98%	94%	89%	83%	76%	68%	61%	53%	46%	39%	33%	27%	23%	19%	15%	12%	8%	6%	3%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
33.1°	66°	77.6°	98.7%	98.0%