

Light efficiency:

101 Lumen/Watt

Light quality:

CRI: 81.9

Color temperature:


3024 K

Output: 4006 lm

Peak: 2184 cd

Power: 39.8 W


PF: 0.98



NU6-QD-SW-45LM-30K-80-HE85-WH-WH

Date and time:

9/7/2022 11:37:35 AM




Beam angle

86.2°






CIE 1931
x: 0.437
y: 0.407

Spectra




Power







TM30: 83.8



CRI: 81.9 (R1-R8)



CQS: 81.2



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
79.9	88.5	96.0	81.1	79.6	85.4	84.2	60.2	6.6	73.5	80.2	66.9	81.7	97.6	72.1

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
80.1	80.7	75.6	84.6	90.6	90.4	84.4	91.8	89.1	82.3	79.9	84.0	88.5	81.6	79.0	79.2

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
76.8	96.1	80.7	78.9	81.7	81.2	81.7	85.7	96.1	87.5	85.0	83.1	82.3	70.4	72.5

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3024 K	81.9	6.6	83.8	97.3	81.2	0.437	0.407	0.249	0.348	0.0010







Rf 83.8


Fidelity index Rf

Rg 97.3

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	80	-11%	-2%
2	81	-9%	7%
3	76	-3%	13%
4	85	3%	9%
5	91	5%	5%
6	90	5%	-3%
7	84	-1%	-10%
8	92	-3%	-4%
9	89	-7%	0%
10	82	-7%	7%
11	80	-3%	14%
12	84	6%	6%
13	88	6%	-4%
14	82	7%	-13%
15	79	-1%	-14%
16	79	-7%	-15%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2184lx	546lx	243lx	136lx	87lx	61lx	45lx	34lx	27lx	22lx	18lx	15lx	13lx	11lx	10lx	9lx	8lx	7lx	6lx	5lx
202.9fcd	50.7fcd	22.5fcd	12.7fcd	8.1fcd	5.6fcd	4.1fcd	3.2fcd	2.5fcd	2fcd	1.7fcd	1.4fcd	1.2fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
2184	2172	2133	2069	1978	1862	1708	1482	1168	792	510	369	276	190	117	72	41	16	1	1
100%	99%	98%	95%	91%	85%	78%	68%	53%	36%	23%	17%	13%	9%	5%	3%	2%	1%	0%	0%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
2184	2171	2132	2068	1977	1858	1703	1478	1165	787	504	367	274	188	115	71	40	17	1	1
100%	99%	98%	95%	91%	85%	78%	68%	53%	36%	23%	17%	13%	9%	5%	3%	2%	1%	0%	0%

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
2184	2172	2133	2069	1978	1862	1708	1482	1168	792	510	369	276	190	117	72	41	16	1	1
100%	99%	98%	95%	91%	85%	78%	68%	53%	36%	23%	17%	13%	9%	5%	3%	2%	1%	0%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
2184	2171	2132	2068	1977	1858	1703	1478	1165	787	504	367	274	188	115	71	40	17	1	1
100%	99%	98%	95%	91%	85%	78%	68%	53%	36%	23%	17%	13%	9%	5%	3%	2%	1%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
86.2°	127.5°	155.4°	92.5%	75.1%