

Light efficiency:

91 Lumen/Watt

Light quality:

CRI: 93.3

Color temperature:

2938 K

Output: 1908 lm

Peak: 4001 cd


Power: 21.1 W

PF: 0.97



NUE4-RD-SW-20LM-30K-90-40D-CL-WH-WH

Date and time:
3/7/2023 3:42:39 PM




Beam angle

41.6°






CIE 1931
x: 0.443
y: 0.409

Spectra




Power






TM30: 92.6



CRI: 93.3 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93.5	95.9	97.7	94.9	93.5	95.9	92.7	82.0	58.0	90.3	96.7	83.9	94.2	98.0	88.3


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
91.2	92.9	90.9	94.5	95.6	95.4	94.1	98.0	96.1	93.5	90.8	90.3	92.0	88.2	92.4	85.9

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
87.9	96.0	90.4	91.8	93.3	92.2	92.6	94.1	97.5	94.8	94.7	94.1	93.4	86.4	86.8

CQS: 91.6



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2938 K	93.3	58.0	92.6	99.8	91.6	0.443	0.409	0.253	0.349	0.0010







Rf 92.6


Fidelity index Rf

Rg 99.8

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	91	-5%	-1%
2	93	-3%	2%
3	91	-1%	5%
4	95	0%	2%
5	96	1%	3%
6	95	3%	0%
7	94	0%	-3%
8	98	1%	-1%
9	96	-2%	1%
10	93	-2%	3%
11	91	1%	6%
12	90	4%	1%
13	92	3%	-5%
14	88	4%	-9%
15	92	-1%	-5%
16	86	-3%	-11%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
3999lx	1000lx	444lx	250lx	160lx	111lx	82lx	62lx	49lx	40lx	33lx	28lx	24lx	20lx	18lx	16lx	14lx	12lx	11lx	10lx
371.6fcd	92.9fcd	41.3fcd	23.2fcd	14.9fcd	10.3fcd	7.6fcd	5.8fcd	4.6fcd	3.7fcd	3.1fcd	2.6fcd	2.2fcd	1.9fcd	1.7fcd	1.5fcd	1.3fcd	1.1fcd	1fcd	0.9fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3999	3988	3938	3848	3727	3570	3376	3143	2865	2537	2149	1734	1326	977	696	495	354	243	164	110
100%	100%	98%	96%	93%	89%	84%	79%	72%	63%	54%	43%	33%	24%	17%	12%	9%	6%	4%	3%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3999	3984	3937	3853	3732	3573	3379	3147	2872	2541	2160	1741	1333	973	695	493	352	249	168	112
100%	100%	98%	96%	93%	89%	84%	79%	72%	64%	54%	44%	33%	24%	17%	12%	9%	6%	4%	3%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3999	3988	3938	3848	3727	3570	3376	3143	2865	2537	2149	1734	1326	977	696	495	354	243	164	110
100%	100%	98%	96%	93%	89%	84%	79%	72%	63%	54%	43%	33%	24%	17%	12%	9%	6%	4%	3%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3999	3984	3937	3853	3732	3573	3379	3147	2872	2541	2160	1741	1333	973	695	493	352	249	168	112
100%	100%	98%	96%	93%	89%	84%	79%	72%	64%	54%	44%	33%	24%	17%	12%	9%	6%	4%	3%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
41.6°	62.7°	77.2°	99.4%	98.5%